

1K Primer filler - Primer Shade

Recommended for repairing small damaged areas / spot repairs and painting parts, as an anti-corrosion primer or primer surfacer. Suitable surfaces: Steel, galvanised steel, aluminium, GRP, hardened old paint, spare part primer, polyester surfaces. (Do not coat with polyester or EP-products).

Advantages

- Can be used on all metal surfaces
- Excellent adhesion, high anticorrosion protection
- High filling capacity
- Can be used variably, either as a primer or surfacer
- Available in various levels of brightness (to match the brightness of the base coat/top coat)
- Can be painted over with waterbased or solvent paints
- Wet-on-wet processing possible
- Smooth flow properties, fast drying
- Easy to sand
- Ideal for spot repairs (especially on sanded-through areas)
- Less paint needed thanks to optimised structure and optimised process times

Article number

680271 white (400 ml)

680272 light grey (400 ml)

680274 medium grey (400 ml)

680276 dark grey (400 ml)

680277 black (400 ml)

680278 beige (400 ml)



Variator


Primers / fillers

Application notes



Spray pass

1 - 3 passes each approx.
15 µm



Flash-off time

flash off time: 3 - 5 min
overcoatable: 25 min /
20°C



Drying „Infrared device“

IR: 7 min



Sanding 'Wet / dry'(manually)

P400 - P500

For further information, please refer to the safety data sheets / technical information sheets

Substrate

Steel, Zinc / galvanised steel, Alu / non-ferrous metal, Plastics, Putty, KTL, Old paintwork

Industries

Automotive, Industry