Material base

Substrate

VOC Value (EU)

Product

Properties

Description / Purpose

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96 74831 Gundelsheim / Deutschland Telefon: +496269 95-0, Fax: +496269 95-80 www.spraymax.com / www.kwasny.com / info@kwasny.de

SprayMax® 1K Aqua Silicon remover 400 ml Art. Nr. 680094

Water-borne cleaning agent, rich in active ingredients and with a reduced solvent content. Ideal for the removal of silicone, grease, oil, wax, dirt, tar, and soot. This high quality product improves the adhesion to any paint coat and reduces the electrostatic effect. High cleaning and degreasing properties. The product is used for the application of waterborne basecoats.

- Increases adhesion
- Maximum yield
- Uniform distribution
- · Strong cleaning and degreasing effect
- Reduces electrostatic effect
- · Espacially for application of waterborne basecoats and special coatings.

Combination of water and and solvent resins 687 g/l

Metal, plastics, glass, old paint and factory paintol which have been filled and primed; Coated and uncoated surfaces.







Processing

Protection measures

Spraying distance


Spray passes

Processing conditions

Finish

Wear personal protection equipment. (respiratory mask/gloves/goggles) For more information, see safety data sheet.

15 cm - 20 cm



1 light spray coat directly before you applying the next paint coat and wipe it immediately using a clean, dry cloth. Only clean small areas in parallel. In case of heavy contamination repeat the cleaning process. Don't use contaminated clothes. Change the clothes more often.

Optimum application at 18° C - 25° C and a relative humidity from 40 - 60 %.

After painting, turn the can upside down and spray the valve until empty.

Additional Information

Shelf Life



60 months

The usage period refers to an unused can that is stored correctly at a temperature of 15 - 25° C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.



Note

For professional use only. Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.